ADHERO® Floor Drain

Floor drain as part of the SOLITEX ADHERO system



Technical data

	Material
Main component	PVC

Property	Regulation	Value
Colour		Grey
Thickness		3.5 mm ; 1/8"
Height		320 mm ; 12⅝"
Outer diameter		Flange: 300 mm ; 11 13/16"
Outer diameter		Pipe: 63 mm ; 2½"

Areas of application

Flange-shaped accessory for vertical drainage through a floor or roof structure during the construction phase. Installation with connection to a pipe or tube system for temporary drainage of water.

Supply forms

Art. no.	For ⌀ pipe	Length	Width	Contents	Weight	GTIN
1AR03200	63 mm	300 mm	300 mm	1 piece	0.52 kg	4026639232007

Advantages

- ✔ Quick installation: simply drill through the building structure, no cutting necessary
- ✔ Dependable drainage: reliable run-off thanks to extra-flat flange with minimal height
- ✔ Watertight sealing: transition between SOLITEX ADHERO and Floor Drain can be sealed with TESCON VANA with SOLID adhesive with TESCON VANA adhesive tape with SOLID adhesive
- ✔ Time-saving and reliable drainage: connection to pipes and tubes for temporary drainage

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Germany at +49 6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
Phone: +49 6202 2782 0
eMail: info@proclima.com