AEROFIXX + AEROBOXX

Application gun for AEROSANA system foil cartridges – with transport case



Technical data

	Material
Main component	Stable aluminium pressure cylinder, ergonomic nylon handle, case: PP

Property	Regulation	Value
Length		600 mm ; 23⅝"
Width		400 mm ; 15¾"
Height		223 mm ; 8¾"
Weight		6.25 kg ; 13.78 lb

Areas of application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from foil cartridges onto smooth and rough mineral and non-mineral substrates such as timber, wood fibreboards, OSB, stone, plaster, concrete etc. Suitable for compressors with a suction flow rate of at least 300 l/min.

Includes a transport case. The case has enough space for a range of accessories and can be modified for the user's needs thanks to the flexible padding arrangement.

Supply forms

Art. no.	Length	Width	Height	Weight	GTIN
1AR04695	600 mm	400 mm	223 mm	5.6 kg	4026639246950

Advantages

- ✔ Work more quickly: application and spreading of liquid sealant in a single working step
- ✔ Precise application of sealant: setting 1 for a line of sealant to fill joints, setting 2 to spray over and seal surfaces
- ✔ Allows the installer to work with one hand
- ✔ No brush required
- ✔ Pressure: up to 6.8 bar (100 psi)
- ✔ Safe transportation: all components and accessories fit in a single case

General conditions

The AEROFIXX device is connected to a compressor with a suction flow rate of >300 l/min. The pressure should be set to 6 bar. All AEROSANA VISCONN products in 600 ml (20.3 US fl oz) foil cartridges can be applied using the AEROFIXX device. You can easily switch between line application and spray application by turning the spray head.

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Germany at +49 6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
Phone: +49 6202 2782 0
eMail: info@proclima.com