AEROSANA® FLEECE

Fleece for covering cracks or joints



Technical data

	Material
Main component	PET

Property	Regulation	Value
Colour		White
Surface weight		63 g/m² ; 0.21 oz/ft²
Thickness		0.7 mm ; 28 mils
Tensile strength MD/CD		90 N/5 cm / 145 N/5 cm ; 10 lb/in / 17 lb/in
Elongation MD/CD		75 % / 90 %
Application temperature		5 °C to 60 °C ; 40 °F to 140 °F

Areas of application

AEROSANA FLEECE is a supplementary product for working with spray-on or brush-on sealants from the AEROSANA VISCONN series.

It can be used to reliably cover cracks or joints that are wider than 3 mm (⅛") in the case of AEROSANA VISCONN or 20 mm (¾") in the case of AEROSANA VISCONN FIBRE.

Supply forms

Art. no.	Length	Width	Weight	Sales unit	Container	GTIN
1AR01715	25 m	150 mm	0.624 kg	1	90	4026639217158

Advantages

- ✔ Reliable airtightness and windtightness: Tested as part of the AEROSANA VISCONN system
- ✔ Easy to work with: Very malleable fleece material
- ✔ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

AEROSANA FLEECE can be used on subsurfaces that are slightly uneven and/or structured. To achieve airtight and/or windtight installation, it is important that AEROSANA FLEECE is coated with AEROSANA VISCONN or AEROSANA VISCONN FIBRE on both sides in the area where it is in contact with the subsurface. Recommendations for subsurfaces that AEROSANA VISCONN products can be used on can be found in the relevant application recommendations.

Tested for hazardous substances according to ISO 16000

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Germany at +49 6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
Phone: +49 6202 2782 0
eMail: info@proclima.com