CONTEGA® SOLIDO EXO

Full-surface adhesive plaster/window-sealing tape, for exterior use



Technical data

	Material
Backing	PP backing fleece, PP copolymer special film
Adhesive	Modified water-resistant SOLID adhesive
Release film	Single/double-split silicone-coated PE sheet

Property	Regulation	Value
Colour		Black
sd value	EN 1931	0.7 m
g value	EN 1931	3.5 MN·s/g
Vapour permeance	ASTM E 96	4.7 US perms
Outdoor exposure		3 months
Resistance to driving rain	EN 1027	Up to 2400 Pa, around windows
Resistance to driving rain	ift, MO-01/1:2007-01, Abs. 5	Up to 600 Pa, around windows
Water column	EN ISO 811	> 2 500 mm ; > 8' 2"
Bond durability, non-aged/aged	EN 17990	Passed
Can be plastered over		Yes
Application temperature		Above -10 °C ; 14 °F
Temperature resistance, permanent		-40 °C to 90 °C ; -40 °F to 194 °F
Storage		Cool and dry

Areas of application

For exterior windtight joints that are resistant to driving rain between membranes or wood-based panels and windows, doors and mineral surfaces. The modified water-resistant SOLID adhesive ensures quick and permanent adhesion to the subsurface. The taped joint is immediately windproof and can be subjected to loading. The fleece can simply be plastered over in accordance with the installation instructions.

Splits on release film

Tape width	Split (approx.)
80 mm (3⅛")	20 | 60 mm (⅞" | 2⅜")
100 mm (4")	20 | 40 | 40 mm (⅞" | 1⅝" | 1⅝")
150 mm (5⅞")	20 | 70 | 60 mm (¾" | 2¾" | 2⅜")
200 mm (7⅞")	20 | 100 | 80 mm (¾" | 4" | 3⅛")

Supply forms

Art. no.	Length	Width	Release film splits	Weight	Sales unit	Container	GTIN
15439	30 m	80 mm	20 | 60 mm	0.98 kg	8	384	4026639154392
15440	30 m	100 mm	20 | 40 | 40 mm	1.1 kg	8	288	4026639154408
15441	30 m	150 mm	20 | 70 | 60 mm	1.8 kg	4	192	4026639154415
15442	30 m	200 mm	20 | 100 | 80 mm	2.4 kg	4	144	4026639154422

Advantages

- ✔ Saves time: the joint is immediately resistant to driving rain and can be subjected to loading
- ✔ Can be plastered over directly: defined transition between window and/or wind sealing and plasterwork
- ✔ Reliable joints: water-resistant SOLID adhesive has extremely strong adhesion on mineral subsurfaces too
- ✔ Proven resistance to driving rain up to 2400 Pa
- ✔ Independently confirmed suitability: tests in accordance with MO-01/1 passed at IFT in Rosenheim, Germany

Substrates

Clean subsurfaces before applying tape. Fine dust and any loose fibres must be thoroughly removed by vacuuming. Uneven mineral subsurfaces may need to be levelled with a smooth plaster finish. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied.

Observe the recommendations for plastering over adhesive tapes that are specified by the producer of the plaster. In most cases, it is recommended that the width of adhesive tape that is to be plastered over should not exceed 60 mm (2⅜") or 50% of the reveal area. Subsurfaces must be sufficiently dry and stable; if necessary, subsurfaces should be stabilised or renewed.

Permanent adhesion is achieved on all pro clima interior membranes and on other vapour control and airtight membranes (e.g. those made of PE, PA, PP and aluminium). Tapes can be applied to planed or painted wood, gypsum fibreboards, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels). For sealing joints on masonry or concrete or on rough substrates, use ORCON F.

Particular care is necessary when working with older or multi-layer subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces with insufficient stability. No pre-treatment with primer is required on gypsum fibreboards if their surfaces have been cleaned and are dust-free.

General conditions

Taped joints should not be subjected to tensile strain. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Seals that are windproof and resistant to driving rain can only be achieved if the sealing tape is installed free of folds and breaks.
When plastering, please observe the recommendations of the plaster manufacturer for non-absorbent subsurfaces. A bonding course may be necessary.

EPD verified

© ift Rosenheim
Prüfbericht Nr. 16-000527-PR02
(PB 1-E03-020310-de-01)
- CONTEGA SOLIDO SL
- CONTEGA SOLIDO EXO
nach MO-01/1:2007-01, Abs. 5
24.06.2016

NBS

NSAI Agrément
pro clima Intelligent Airtight System
CERT No. 07/0297

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Germany at +49 6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
Phone: +49 6202 2782 0
eMail: info@proclima.com