# STOPPA

## Airtight plugs for ducts for interior and exterior use



### Technical data

| Material | |
|---|---|
| Main component | Thermoplastic elastomer (TPE) |

| Property | Regulation | Value |
|---|---|---|
| Colour | | Blue |
| Application temperature | | > -10 °C ; 14 °F |
| Temperature resistance, permanent | | -50 °C to 90 °C ; -58 °F to 194 °F |
| Storage | | Cool and dry |

### Areas of application

For the quick and lasting, secure airtight installation of cables in ducts. Conduit grommets (e.g. ROFLEX Ø 15-30 mm) are available for the airtight connection of ducts to the vapour control and airtight membrane.

### Supply forms

| Art. no. | For ⌀ pipe | Contents | Weight | GTIN |
|---|---|---|---|---|
| 12945 | OD 16 mm (5/8") \| ID 11 mm (7/16") | 20 pieces | 0.1 kg | 4026639129451 |
| 12947 | OD 20 mm (7/8") \| ID 15 mm (9/16") | 20 pieces | 0.13 kg | 4026639129475 |
| 12949 | OD 25 mm (1") \| ID 19.5 mm (3/4") | 20 pieces | 0.13 kg | 4026639129499 |
| 12951 | OD 32 mm (1 1/4") \| ID 25 mm (1") | 20 pieces | 0.2 kg | 4026639129512 |
| 12953 | OD 40 mm (1 5/8") \| ID 31.5 mm (1 1/4") | 20 pieces | 0.2 kg | 4026639129536 |

### Advantages

- ✔ Ensures cables in ducts are sealed
- ✔ Standards-compliant construction: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✔ Simple insertion: press-out membrane creates a reliable seal with cable
- ✔ Easy to work with: holes can be pre-formed with a nail or nozzle tip
- ✔ Also suitable for several cables
- ✔ Reliable air sealing to profiled pipes thanks to multiple lip sealing
- ✔ Can be easily removed if a new cable is to be installed
- ✔ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ A+ A B C

*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes missions)

Tested for hazardous substances according to ISO 16000

Made in Germany developed and produced by pro clima

The applications and conditions described here are based on current research findings and practical experience. We reserve the right to change the recommended application designs and installation methods and to develop and thus change the properties and quality of individual products. We would be glad to inform you about the current state of engineering knowledge at the time that your installation is carried out.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Germany at +49 6202 278245.

**MOLL**
**bauökologische Produkte GmbH**
Rheintalstraße 35 - 43
68723 Schwetzingen
Germany
Phone: +49 6202 2782 0
eMail: info@proclima.com