# Declaration of Performance

① DA

② 10098
(Batch number - see imprint on membrane)

Vapour-check and airtightness membrane, suitable for all fibrous insulation materials

④ MOLL bauoekologische Produkte GmbH
Rheintalstrasse 35 - 43
68723 Schwetzingen
Germany

System 3

The notified body "MPA Dresden GmbH" - NB 0767 - carried out the initial tests of the material properties according to system 3.

### ⑨ Performance declared according to EN 13984 - Typ A

| Property | Standard | Value |
|---|---|---|
| Length[1] | EN 1848-2 | 50 m |
| Width[2] | EN 1848-2 | 1.5 m |
| Surface weight | EN 1849-2 | 130 ±5 g/m² ; 0.43 ±0.02 oz/ft² |
| Thickness | EN 1849-2 | 0.45 ±0.05 mm ; 18 ±2 mils |
| sd value | EN 1931 | 2.30 ±0.25 m |
| g value | EN 1931 | 11.5 ±1.25 MN·s/g |
| Reaction to fire classification | EN 13501-1 | E |
| Watertightness to liquid water | EN 1928 | W1 |
| Resistance to impact | EN 13984 | NPD (no performance declared) |
| Tensile strength MD/CD | EN 12311-2 | 230 N/5 cm / 200 N/5 cm ; 26 lb/in / 23 lb/in |
| Elongation MD/CD | EN 12311-2 | 90% / 90% |
| Nail tear-resistance MD/CD | EN 12310-1 | 120 N / 115 N ; 27 lbf / 26 lbf |
| Joint strength | EN 12317-2 | NPD (no performance declared) |
| Durability after artificial ageing | EN 1296 / EN 1931 | Passed |
| Resistance to chemicals | EN 13984 | NPD (no performance declared) |
| Dangerous substances | EN 13984 | None |

dimensional tolerances: [1]: +0.5 m; [2]: +0.005 m

The performance of the product according to numbers 1 and 2 corresponds to the performance declared according to number 9. According to number 4, the manufacturer is solely responsible for issuing this Declaration of Performance. Signed for the manufacturer and on behalf of the manufacturer by:



Lothar Moll, CEO



Michael
Förster, technical manager

Schwetzingen, 11/05/2026