Declaration of Performance

① DASAPLANO 0,01 connect

② 14086
(Batch number - see imprint on membrane)

Airtightness membrane for roof refurbishment

④ MOLL bauoekologische Produkte GmbH
Rheintalstrasse 35 - 43
68723 Schwetzingen
Germany

System 3

The notified body "Gesellschaft für Materialforschung und Prüfungsanstalt für Bauwesen mbH" - NB 0800 - carried out the initial tests of the material properties according to system 3.

⑨ Performance declared according to EN 13984 - Typ A

Property	Standard	Value
Length[1]	EN 1848-2	50 m
Width[2]	EN 1848-2	1.5 m
Surface weight	EN 1849-2	145 ±5 g/m² ; 0.48 ±0.02 oz/ft²
Thickness	EN 1849-2	0.50 ±0.05 mm ; 20 ±4 mils
Reaction to fire classification	EN 13501-1	E
Watertightness to liquid water	EN 1928	W1
Resistance to impact	EN 13984	NPD (no performance declared)
Tensile strength MD/CD	EN 12311-2	270 N/5 cm / 200 N/5 cm ; 31 lb/in / 23 lb/in
Elongation MD/CD	EN 12311-2	55% / 70%
Nail tear-resistance MD/CD	EN 12310-1	150 N / 150 N
Joint strength	EN 12317-2	NPD (no performance declared)
Durability after artificial ageing	EN 1297 / EN 1296	Passed
Resistance to chemicals	EN 13984	NPD (no performance declared)
Dangerous substances	EN 13984	None

dimensional tolerances: [1]: +0.5 m; [2]: +0.005 m

The performance of the product according to numbers 1 and 2 corresponds to the performance declared according to number 9. According to number 4, the manufacturer is solely responsible for issuing this Declaration of Performance. Signed for the manufacturer and on behalf of the manufacturer by:

Lothar Moll, CEO

Michael Förster, technical manager

Schwetzingen, 11/05/2026