



Technical data

Material	
Main component	PET

Property	Regulation	Value
Colour		White
Surface weight		63 g/m ² ; 0.21 oz/ft ²
Thickness		0.7 mm ; 28 mils
Tensile strength MD/CD		90 N/5 cm / 145 N/5 cm ; 10 lb/in / 17 lb/in
Elongation MD/CD		75 % / 90 %
Installation temperature		5 °C to 60 °C ; 40 °F to 140 °F

Areas of application

AEROSANA FLEECE is a supplementary product for working with spray-on or brush-on sealants from the AEROSANA VISCONN series. It can be used to reliably cover cracks or joints that are wider than 3 mm (1/8") in the case of AEROSANA VISCONN or 20 mm (3/4") in the case of AEROSANA VISCONN FIBRE.

Supply forms

Art. no.	GTIN	Length	Width	Weight	Sales unit	Container
1AR01715	4026639217158	25 m	150 mm	0.624 kg	1	90

Advantages

- ✓ Reliable airtightness and windtightness: Tested as part of the AEROSANA VISCONN system
- ✓ Easy to work with: Very malleable fleece material
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme

Substrates

AEROSANA FLEECE can be used on subsurfaces that are slightly uneven and/or structured. To achieve airtight and/or windtight installation, it is important that AEROSANA FLEECE is coated with AEROSANA VISCONN or AEROSANA VISCONN FIBRE on both sides in the area where it is in contact with the subsurface. Recommendations for subsurfaces that AEROSANA VISCONN products can be used on can be found in the relevant application recommendations.

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

MOLL