

# AEROFIXX + AEROBOXX

Application gun for AEROSANA system foil cartridges – with transport case



## Technical data

Material		
Main component	Stable aluminium pressure cylinder, ergonomic nylon handle, case: PP	
Property	Regulation	Value
Length		600 mm ; 23 5/8"
Width		400 mm ; 15 3/4"
Height		223 mm ; 8 3/4"
Weight		6.25 kg ; 13.78 lb

## Areas of application

For particularly quick and easy application of the AEROSANA VISCONN and AEROSANA VISCONN FIBRE sealants from foil cartridges onto smooth and rough mineral and non-mineral substrates such as timber, wood fibreboards, OSB, stone, plaster, concrete etc. Suitable for compressors with a suction flow rate of at least 300 l/min.

Includes a transport case. The case has enough space for a range of accessories and can be modified for the user's needs thanks to the flexible padding arrangement.

## Supply forms

Art. no.	GTIN	Contents	Weight
1AR04695	4026639246950	1 pieces	5.6 kg

## Advantages

- ✓ Work more quickly: application and spreading of liquid sealant in a single working step
- ✓ Precise application of sealant: setting 1 for a line of sealant to fill joints, setting 2 to spray over and seal surfaces
- ✓ Allows the technician to work with one hand
- ✓ No brush required
- ✓ Pressure: up to 6.8 bar (100 psi)
- ✓ Safe transportation: all components and accessories fit in a single case

## General conditions

The AEROFIXX device is connected to a compressor with a suction flow rate of >300 l/min. The pressure should be set to 6 bar. All AEROSANA VISCONN products in 600 ml (20.3 US fl oz) foil cartridges can be applied using the AEROFIXX device. You can easily switch between line application and spray application by turning the spray head.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

---

**MOLL**

**bauökologische Produkte GmbH**

Rheintalstraße 35 - 43

D-68723 Schwetzingen

Fon: +49 (0) 62 02 - 27 82.0

eMail: [info@proclima.de](mailto:info@proclima.de)