

CONTEGA SOLIDO EXO-D

Full-surface adhesive plaster sealing tape for exterior use with an additional adhesive zone on the fleece side



Technical data

Substance		
Backing	PP backing fleece, PP copolymer special membrane	
Adhesive	modified waterproof SOLID adhesive / special acrylate adhesive	
Release film	one or two split silicone-coated PE sheet	
Attribute	Regulation	Value
Colour		black
sd-value	EN 1931	0.7 m
g-value		3.5 MN·s/g
Vapour permeance	ASTM E 96	4.7 US perms
Exposure time		3 months
Water column	EN 20811	> 2 500 mm ; > 8' 2"
Resistance to driving rain	ift, MO-01/1:2007-01, Abs. 5	up to 600 Pa, surrounding
Bonding requirement, non-aged/aged	DIN 4108-11	passed
Can be plastered over		yes
Application temperature		above -10 °C ; 14 °F
Temperature resistance		permanent -40 °C to 90 °C ; -40 °F to 194 °F
Storage		cool and dry

Area of application

The CONTEGA SOLIDO EXO-D joint adhesive tape, which is full-surface adhesive and can be plastered over, ensures windtight and diffusion-permeable exterior sealing of windows and doors to adjacent building components made of wood and mineral substrates such as concrete and masonry.

The integrated adhesive zone on the fleece side allows for easy adhesion to windows and doors.

The stuck joint is immediately windproof and can be subjected to loading. The fleece can simply be plastered over in accordance with our application guide.

Advantages

- ✓ The joint is immediately windproof and resistant to driving rain as a result of full-surface adhesion
- ✓ Extremely strong adhesion on mineral substrates too thanks to SOLID adhesive
- ✓ Can be plastered over
- ✓ Simple adhesion
- ✓ Easy to apply

Substrates

Before adhesion is carried out, substrates should be brushed off, wiped clean with a cloth or cleaned using compressed air.

Uneven mineral substrates may need to be levelled with a smooth finish.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded.

Substrates must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima exterior membranes and on other underlay/sarking and wall lining membranes (e.g. those made of PP and PET).

Adhesion can be carried out on planed and painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels) and on mineral substrates such as concrete and masonry.

The best results in terms of structural stability are achieved on high-quality substrates.

It is your responsibility to check the suitability of the substrate; adhesion tests are recommended in certain cases.

Pretreatment with TESCON PRIMER is recommended in the case of substrates with insufficient stability.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de




General conditions

The bonds should not be subjected to tensile strain.

Press firmly to secure the adhesive tapes in place. Ensure that there is sufficient resistance pressure.

Seals that are windproof and resistant to driving rain can only be achieved if the sealing tape is installed free of folds and breaks.



Prüfbericht Nr. 15-003305-PR01
(PB-E03-020310-de-02)

• CONTEGA SOLIDO SL-D
• CONTEGA SOLIDO EXO-D
nach MO-01/1:2007-01, Abs. 5
15.03.2016

**Made in
Germany**



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

