

TESCON NAIDECK mono patch

Single-sided nail-sealing patch



Technical data

Material		
Backing	PE film	
Adhesive	Butyl rubber modified with acrylate	
Release film	Silicone-coated PE film	
Property	Regulation	Value
Colour		Butyl rubber: grey, film: black
Thickness		1.1 mm ; 43 mils
Outdoor exposure		6 months, installed under the counter battens
Installation temperature		-10 °C to 35 °C ; 14 °F to 95 °F
Temperature resistance		Permanent -40 °C to 80 °C ; -40 °F to 176 °F
Storage		Cool and dry

Areas of application

For use underneath counter battens on pitched roof constructions. TESCO NAIDECK mono patch is suitable for use in creating temporary coverings in accordance with the product data sheets of the Central Association of the German Roofing Trade (ZVDH) for roofing underlays membranes. 300 patches per roll.

Supply forms

Art. no.	GTIN	Length	Width	Contents	Weight	Sales unit
1AR02157	4026639221575	86 mm	62 mm	300 pieces	3 kg	4

Advantages

- ✓ Very good sealing effect: sealing material is pulled into the hole created when a nail or screw is fitted
- ✓ Easy to pre-install on roofing underlays or battens
- ✓ Conforms to regulations: satisfies the requirements of the German ZVDH trade association and of the Swiss SIA 232/1 standard
- ✓ Material savings: patch is only stuck to the counter batten in the area around the nail/screw
- ✓ Reliable during the construction phase: suitable as a temporary covering during the construction period

Substrates

Clean subsurfaces before sticking. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded. Subsurfaces must be sufficiently dry and stable.

TESCON NAIDECK mono patch can be used on all pro clima exterior membranes, on other underlay and breather (WRB) membranes (e.g. those made of PP and PET) and with MDF panels and wood-fibre underlay panels.

The best results in terms of structural stability are achieved on level, unstructured subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases. Pre-treatment with TESCO PRIMER is recommended in the case of subsurfaces with insufficient stability.

General conditions

Perforation seals and water-resistant adhesive joints will only be effective on roofing underlay membranes that have been installed with no folds or creases. This patch can be stuck onto the counter batten or the substrate that is to be sealed. Rub the patch firmly to secure the adhesive bond.

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Phone: +49 (0) 62 02 - 27 82.0
E-mail: info@proclima.com

