

STOPPA

Airtight plugs for ducts for interior and exterior use



Technical data

Material		
Main component	Thermoplastic elastomer (TPE)	
Property		
Colour	Regulation	Value
Conduit outer diameter		16 mm ; 0.63"
Conduit inner diameter		11 mm ; 0.43"
Installation temperature		> -10 °C ; 14 °F
Temperature resistance		permanent -50 °C to 90 °C ; -58 °F to 194 °F
Storage		Cool and dry

Areas of application

For the quick and lasting, secure airtight installation of cables in ducts. Conduit grommets (e.g. ROFLEX 20 or ROFLEX 20 multi) are available for the airtight connection of ducts to the vapour check and airtight membrane.

Supply forms

Art. no.	GTIN	Contents	Weight
12945	4026639129451	20 pieces	0.1 kg

Advantages

- ✓ Ensures cables in ducts are sealed
- ✓ Construction in adherence with standards: for airtight sealing in accordance with DIN 4108-7, SIA 180 and RE 2020
- ✓ Simply insertion: press-out membrane creates a reliable seal with cable
- ✓ Easy to work with: holes can be pre-formed with a nail or nozzle tip
- ✓ Also suitable for several cables
- ✓ Reliable air sealing to profiled pipes thanks to multiple lip sealing
- ✓ Can be easily removed if a new cable is to be installed
- ✓ Excellent values in hazardous substance testing, has been tested according to the ISO 16000 evaluation scheme



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

Tested for hazardous substances according to



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

MOLL
bauökologische Produkte GmbH