

# MOLL

## Declaration of Performance

### ① **CONSTIVAP 2.3 PLUS**

② 15822

(Batch number - see imprint on membrane)

Vapour-check and airtightness membrane, suitable for all fibrous insulation materials

④ MOLL bauökologische Produkte GmbH  
Rheintalstraße 35 - 43  
68723 Schwetzingen  
Germany

System 3

The notified body "Gesellschaft für Materialforschung und Prüfungsanstalt für Bauwesen mbH" - NB 0800 - carried out the initial tests of the material properties according to system 3.

#### ⑨ **Performance declared according to BS EN 13984 - Typ B**

Property	Standard	Value
Length <sup>1</sup>	BS EN 1848-2	50 m
Width <sup>2</sup>	BS EN 1848-2	1.5 m
Surface weight	BS EN 1849-2	90 ±5 g/m <sup>2</sup>
Thickness	BS EN 1849-2	0.2 ±0.05 mm
sd value	BS EN 1931	2.30 ±0.25 m
g value		11.5 ±1.25 MN·s/g
Fire class		E
Tensile strength MD/CD	BS EN 13859-1	355 N/5 cm / 285 N/5 cm
Elongation MD/CD	BS EN 12311-2	15 % / 15 %
Nail tear resistance MD/CD	BS EN 13859-1	240 N / 200 N
Durability after artificial ageing	BS EN 1296 / BS EN 1931	Passed

dimensional tolerances: <sup>1</sup>: +0.5 m; <sup>2</sup>: +0.005 m

The performance of the product according to numbers 1 and 2 corresponds to the performance declared according to number 9. According to number 4, the manufacturer is solely responsible for issuing this Declaration of Performance. Signed for the manufacturer and on behalf of the manufacturer by:



Lothar Moll, Geschäftsführer



Michael Förster, Leiter Technik

Schwetzingen, 01/02/2025