

Sealant Compatibility & Adhesion Matrix

All tests were conducted by the sealant manufacturer concerned. Pro Clima recommends carrying out a field adhesion test prior to sealant application to check adhesion to the substrate is satisfactory. Refer to the manufacturer's literature for information regarding the installation and preparation requirements of the selected sealant.

Sealant type	PRO CLIMA PRODUCT				
	TESCON EXTOSEAL® Sill Tape	TESCON EXTORA® Flashing Tape	SOLITEX EXTASANA® / MENTO® 3000 Underlay	SOLITEX EXTASANA ADHERO® Underlay	SOLITEX MENTO® 1000 Underlay
APTC Proflex Hy	Ⓣ	○	○	○	○
Bostik MS Safe Seal	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Bostik Seal 'N' Flex Façade	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
DOWSIL 688	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
DOWSIL 758	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
DOWSIL 790	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
DOWSIL 791	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Gorilla 940FC	Ⓣ	○	○	○	○
Gorilla Blackjack Sealant	Ⓣ	○	○	○	○
Gorilla Plumbers Silicone	Ⓣ	○	○	○	○
Gorilla MS Sealant	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Glasscorp MSHP	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Glasscorp HP Façade	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sabreseal MS25	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sabreseal NC	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sabreseal NC45	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sika AT Façade	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sika MS	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sikaflex 123 MS Bond	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
SikaHyflex 250 Façade	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Sikasil WS 605 S	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Soudaseal FR	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Soudaseal 240FC	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Soudal Fix All High Tack	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Soudaseal Façade 20LM	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ
Tremco Dymonic FC	Ⓣ	Ⓣ	Ⓣ	Ⓣ	Ⓣ

Ⓣ Tested

○ Not tested

Pro Clima New Zealand Ltd
0800 PRO CLIMA (776 254)
welcome@proclima.co.nz
proclima.co.nz

Pro Clima Australia Pty Ltd
1800 PRO CLIMA (776 254)
welcome@proclima.com.au
proclima.com.au

