

General conditions

- This product should not be exposed to UV or water during the construction or operation of the building.
- Class 2 to Class 3 humidity-variable air barrier.
- Lowest VOC rating in hazardous substance test (ISO 16000).
- Well-protected winter building sites thanks to hydrosafe® behaviour.

PRODUCT DESCRIPTION

INTELLO® PLUS is an air barrier with smart vapour control, forming part of an intelligent airtightness system (IAS) when joints are sealed with TESCON® VANA and junctions are sealed with ORCON® Classic. The INTELLO® PLUS humidity-variable response is achieved by the polyethylene (PE) copolymer laminated on spun-bonded polyethylene (PP) and reinforced with polypropylene mesh.

WEATHER EXPOSURE

This product should not be exposed to UV or water during the construction or operation of the building.

APPLICATION NOTES

INTELLO® PLUS should be installed with the printed side facing the installer, without folds, creases or tears to ensure airtight seals and optimal performance.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

The planning documentation that is available from pro clima provides further information about installation methods and design details. If you have questions, please contact pro clima Technical Support in Australia at 1800 PRO CLIMA (776 254).

MOLL

bauökologische Produkte GmbH

Rheintalstraße 35 - 43

68723 Schwetzingen

Germany

Phone: +49 6202 2782 0

eMail: info@proclima.com