

# Installation instructions

## ROFLEX 20 multi

### Installation steps



#### 1. Preparation

Subsurfaces must have sufficient stability and be dry, level and free of dust, silicone and grease. Brush off subsurfaces; if necessary, clean with a vacuum cleaner and wipe down.



#### 2. Put the template in place

Remove the installation set from its plastic packaging. Place the EPDM grommet on a cardboard underlay. Put the punching template in place and align it with the EPDM grommet so that the edges match.



#### 3. Punch holes

Punch the required number of holes at the markings on the template using a round punch and a hammer.

Note: The subsurface can be damaged by the punching process. If necessary, use a protective layer.



#### 4. Guide the conduits through

Gradually pull the tubes through the grommet. Press the grommet into place so that it rests flat on the subsurface, and align it in place.



#### 5. Stick the grommet

Stick the grommet around its perimeter using the TESCON VANA (or TESCON INVIS) system adhesive tape. Centre the tape and ensure that there is sufficient resistance pressure. Ensure that the overlaps are waterproof in underlay areas (first carry out adhesion at the bottom, then at the left and right, and finally at the top).



#### 6. Rub to secure the adhesive bond

As a final step, rub all adhesive strips firmly to secure the adhesive bond. This work can be carried out more efficiently and in a manner that is kinder to your hands by using the pro clima PRESSFIX application tool. You're finished!

## Substrates

Clean subsurfaces before sticking. Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima interior and exterior membranes, other vapour check and airtight membranes (e.g. those made of PE, PA, PP and aluminium) as well as other roof and breather (WRB) membranes (e.g. those made of PP and PET).

Adhesive bonds are possible on planed and painted wood, hard plastics and metal (e.g. pipes, windows etc.), hard wood-based panels (chipboard, OSB, plywood, MDF and wood-fibre underlay panels). Pre-treatment with TESCON PRIMER is required in the case of adhesion to wood-fibre underlay panels and smooth mineral subsurfaces. Concrete or plaster subsurfaces must not be sandy or crumbling.

The best results in terms of structural stability are achieved on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases. Pre-treatment with TESCON PRIMER is recommended in the case of subsurfaces with insufficient stability.

## General conditions

The bonds should not be subjected to tensile strain. Rub the adhesive tapes firmly to secure the adhesive bonds. Ensure that there is sufficient resistance pressure. Windproof, airtight or rainproof sealing can only be achieved on vapour checks, roofing underlays or breather (WRB) membranes that have been laid without folds or creases. Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary.

---

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about installation and design details is available in the pro clima planning documentation. If you have any questions, please contact [pro clima Technical Support](<https://proclima.com/service/technical-support>).

---

### MOLL

**bauökologische Produkte GmbH**  
Rheintalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
eMail: [info@proclima.de](mailto:info@proclima.de)