



Environmental Product Declaration

In accordance with ISO 14025:2006, EN 15804:2012+A2:2019/AC:2021 for



SOLITEX QUANTHO 3000 connect

**Medium-weight roofing underlay
with self-sealing perforations and waterproof
adhesive strips**

from

pro clima – MOLL bauökologische Produkte GmbH

Products covered by this EPD:

SOLITEX QUANTHO 3000 connect (width: 1.5 m / length: 50 m) GTIN 4026639240767

SOLITEX QUANTHO 3000 connect (width: 3 m / length: 50 m) GTIN 4026639247131

SOLITEX QUANTHO 3000 connect (supplied in project-specific dimensions) GTIN 4026639243997



Programme:	The International EPD System, www.environdec.com
Programme operator:	EPD International AB
Type of EPD	EPD of a specific product
EPD registration number:	EPD-IES-0032695:001
Version date	08/10/2026
Validity date	30/09/2031

An EPD may be updated or depublished if conditions change. To find the latest version of the EPD and to confirm its validity, see www.environdec.com

General information

Programme information

Programme: The International EPD System

Address: EPD International AB
Box 210 60
SE-100 31 Stockholm
Sweden

Website: www.environdec.com

E-mail: support@environdec.com

Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product category rules (PCR): PCR 2019:14 Construction Products, version 2.0.1

UN CPC code: No. 36330: "Plates, sheets, film, foil and strip, of plastics, not self-adhesive, non-cellular and not reinforced, laminated, supported or similarly combined with other materials"

PCR review was conducted by: The Technical Committee of the International EPD System. A full list of members is available on www.environdec.com. The review panel may be contacted via support@environdec.com. Chairs of the PCR review: Rob Rouwette (chair), Noa Meron (co-chair).

Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

☒ Individual EPD verification without a pre-verified LCA/EPD tool

Third party verifier: Jan Weinzettel, weinzettel@seznam.cz

Approved by: The International EPD System

Procedure for follow-up of data during EPD validity involves third-party verifier:

☐ Yes ☒ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but published in different EPD programmes, may not be comparable. For two EPDs to be comparable, they shall be based on the same PCR (including the same first-digit version number) or be based on fully aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have identical scope in terms of included life-cycle stages (unless the excluded life-cycle stage is demonstrated to be insignificant); apply identical impact assessment methods (including the same version of characterisation factors); and be valid at the time of comparison.

For further information about comparability, see EN 15804 and ISO 14025.

Information about EPD owner

Owner of the EPD

pro clima / MOLL bauökologische Produkte GmbH
Rheintalstr. 35-43 – 68723 Schwetzingen – Germany
T: +49 (0) 62 02 – 27 82.0; info@proclima.com

Contact

Michael Förster: support@proclima.com

Life Cycle Assessment (LCA)

LCA accountability: Jannik Schulz, María Díaz Cáceres
brands & values GmbH, info@brandsandvalues.com

Description of the organisation

pro clima is a pioneer in the intelligent, reliable sealing of building envelopes. The company develops and markets product systems for achieving maximum protection against moisture damage to structures and mould:

- Humidity-variable hydrosafe® high-performance vapour check and airtightness membranes for interior sealing on new buildings and renovation projects.
- Roofing underlays and breather membranes (WRBs) with active moisture transport for permanently protected exterior sealing of roofs and walls.
- Special adhesives and waterproof tapes.
- Sealing grommets as detailed solutions.

Highest quality for optimal performance

- The system products are manufactured using state-of-the-art production processes at leading production facilities in Germany.
- Production is subject to the highest quality standards, ensuring that insulation is reliably protected against moisture damage and mould.
- Highest effectiveness of thermal insulation.
- Reduction of heating costs due to optimal air sealing.
- Dry insulation materials.
- Best possible protection against moisture damage to structures and mould.
- Comfortable interiors in summer and winter.
- Healthy indoor climates.

Together towards a successful future

People are the focus of every decision at pro clima, and the company's guiding mission is to advance building culture as a whole. To achieve this goal, system products have been developed for over 30 years that are consistently geared to meet the health and comfort needs of users. Many of pro clima's pioneering developments are now established as state-of-the-art approaches. Today, these products are successfully used in over 40 countries worldwide.

Product-related or management system-related certifications

All production sites are ISO 9001 certified.

Product information



Product name

SOLITEX QUANTHO 3000 connect

Product identification

Roofing underlay with self-sealing perforations and waterproof adhesive strips

Visual representation of the product



UN CPC code

No. 36330: "Plates, sheets, film, foil and strip, of plastics, not self-adhesive, non-cellular and not reinforced, laminated, supported or similarly combined with other materials"

Products covered by this EPD

SOLITEX QUANTHO 3000 connect (width: 1.5 m / length: 50 m) GTIN 4026639240767

SOLITEX QUANTHO 3000 connect (width: 3 m / length: 50 m) GTIN 4026639247131

SOLITEX QUANTHO 3000 connect (supplied in project-specific dimensions) GTIN 4026639243997

This EPD declares a single product — SOLITEX QUANTHO 3000 connect — despite covering multiple GTINs. While all variants are fundamentally the same product, they differ only in their dimensions. These variations meet specific customer requirements but do not alter the product's core environmental characteristics, thus justifying a unified EPD.

Product description

SOLITEX QUANTHO 3000 connect has the following components:

Functional film, front side: Monolithic TPU; Support fleece: Polyester fleece; Self-adhesive strips: Water-resistant SOLID adhesive.

Applications

For use as a diffusion-open roofing underlay over roof sheathing, MDF and wood-fibre underlay panels, and over all thermal insulation materials, including blown-in insulation materials.

Properties

Maximum protection for the roof structure: excellent hail impact resistance as per ETA-23/0532 and VKF (HR 5 class). Reliable rainproof roofs: serves as a sub-roof underlay for roof pitches $\geq 10^\circ$ (2.1:12) with TESCON NAIDECK as an additional sealing measure over rigid substrates, as per ETA-23/0532. Efficient installation: serves as a roofing underlay with waterproof seams and self-sealing perforations for roof pitches $\geq 14^\circ$ (3:12) without the need for additional sealing measures, as per ETA-23/0532. Quick waterproof adhesion: with sealing lip at the 'connect' self-adhesive strips on the long edges of the membrane. Flexible planning of construction schedules: at least 3 months of outdoor exposure. Long-term protection: high resistance to ageing and heat of the functional film. Provides protection during the construction period: suitable as a temporary covering.

Name and location of production site(s)

Manufacturer: pro clima / MOLL bauökologische Produkte GmbH

Location of manufacturing sites: Germany

The declared product is manufactured at two production sites in Germany under contract for pro clima / MOLL bauökologische Produkte GmbH. The cities are not disclosed in this public EPD for reasons of commercial confidentiality, as publication would reveal commercially sensitive supply chain information. The exact production sites are documented in the background report and have been made available to the independent verifier.

Final warehouse and quality control: pro clima / MOLL bauökologische Produkte GmbH, Schwetzingen, Germany

Further information can be found under <https://proclima.com/>

Technical specifications

Property	Regulation	Value
Colour	N/A	Grey-blue
Surface weight	EN 1849-2	230 g/m ² ; 0.75 oz/ft ²
Thickness	EN 1849-2	0.7 mm ; 28 mils
Water vapour resistance factor μ	EN ISO 12572	230
s_d value	EN ISO 12572	0.16 m
g value	N/A	0.8 MN-s/g
Vapour permeance	ASTM E96-A	20.5 perms
Fire class	EN 13501-1	E
Outdoor exposure	N/A	Cen./Nth. Europe & Canada/Nth. US: 4 months ; RoW: 3 months
Hail resistance	EN 13583	ETA-23/0532
Hail impact resistance	VKF / AEAI	Class HR 5
Watertightness of perforation points	EAD 030218-01-0402	ETA-23/0532
Watertight joints with 'connect' adhesive strips or TESCON tape	EN 13859-1	W1
Sarking/roofing underlay membrane (Germany)	ZVDH-Produktdatenblatt 2024	USB / UDB
Suitable as temporary roof covering (Germany)	ZVDH	Yes
Water column	EN ISO 811	> 4 500 mm ; 14' 9"
Watertightness, non-aged/aged*	EN 13859-1	W1 / W1
Tensile strength MD/CD	EN 13859-1 (A)	335 N/5 cm / 355 N/5 cm ; 38 lb/in / 41 lb/in
Tensile strength MD/CD, aged*	EN 13859-1 (A)	325 N/5 cm / 335 N/5 cm ; 37 lb/in / 38 lb/in
Elongation MD/CD	EN 13859-1 (A)	36 % / 55 %
Elongation MD/CD, aged*	EN 13859-1 (A)	36 % / 55 %
Nail tear resistance MD/CD	EN 13859-1 (B)	200 N / 200 N ; 45 lbf / 45 lbf
*) Durability after artificial ageing	EN 1297 / EN 1296	Passed
Flexibility at low temperature	EN 1109	-40 °C ; -40 °F
Temperature resistance	EN 1109, EN 1296, EN 1297	Permanent -40 °C to 100 °C ; -40 °F to 212 °F
Thermal conductivity	N/A	0.04 W/(m·K) ; 0.3 BTU-in/(h·ft ² ·°F)
Emissivity	EN 15976	0.85
CE labelling	ETA-23/0532	Yes

Content declaration

The content declaration refers to the declared unit of 1m² of SOLITEX QUANTHO 3000 connect external windtightness membrane

Product components	Weight, kg	Post-consumer material, weight-%	Biogenic material, weight-% and kg C/kg
Additives	0.007	0.0%	0 %- 0 kg C/kg
Adhesives	0.008	0.0%	0 %- 0 kg C/kg
Film (PE)	0.006	0.0%	0 %- 0 kg C/kg
Non-woven (PET)	0.123	0.0%	0 %- 0 kg C/kg
TPU	0.080	0.0%	0 %- 0 kg C/kg
Printing ink	0.001	0.0%	0 %- 0 kg C/kg
Total product	0.225	0.0%	0 %- 0 kg C/kg
Packaging materials	Weight, kg	Weight-% (relative to the product)	Weight biogenic carbon, [kg C/kg]
Film (PP)	0.003	1.3%	0 kg C/kg
Cardboard	0.005	2.1%	0.002 kg C/kg
Pallet	0.016	6.4%	0.008 kg C/kg
Total packaging	0.025	9.9%	0.01 kg C/kg
TOTAL Product with packaging	0.250	100%	0.01 kg C/kg

The biogenic carbon content of product and packaging is 0.036 kg CO₂ eq. per declared unit.

Dangerous substances from the candidate list of SVHC for Authorisation	EC No.	CAS No.	Weight-% per functional or declared unit
None	Not applicable	Not applicable	Not applicable

LCA information

The EPD conducted is for the specific product SOLITEX QUANTHO 3000 connect external windtightness membrane

Declared unit: 1m² of SOLITEX QUANTHO 3000 connect external windtightness membrane

Conversion factor to mass: 0.2185 kg/m²

Reference service life: 30 years

Time representativeness: Based on yearly manufacturing data from 01/01/2023 until 31/12/2023.

Geographical Scope: Global

Database and LCA software used: For the LCA model, the software system for holistic balancing (LCA for Experts) version 10.9 was used. Background data sets from the current version of the LCA for experts (GaBi) database service pack 2026.1 were used entirely. EN 15804 +A2 (based on EF 3.1) characterisation factors provided in LCA for Experts were applied

Description of the manufacturing processes:


The SOLITEX QUANTHO 3000 connect medium-weight roofing underlay with self-sealing perforations and waterproof adhesive strips is produced by bonding and laminating a TPU functional film layer (front) and a support fleece layer (back) to create large rolls. These rolls are printed and then cut into smaller rolls, which are the sales units. Adhesive strips and release films are fitted to the long edges of the membranes to create the self-adhesive 'connect' strips (one on the printed front surface, one on the back surface). These rolls are then packaged and sent for storage and distribution, first to the central warehouse in Germany, and then all over the world for further sale.

Description of system boundaries:

a) "Cradle to gate with modules C1–C4 and module D"

- The entirety of non-woven fleece polypropylene was modelled as primary material to account for a worst-case scenario.
- All processing steps and locations are balanced within the system boundaries.
- The LCI data manufacturing data was gathered for the specific declared product, and no co-product allocation was necessary.
- The allocation of waste follows the polluter-pays principle. The system boundary to the next product system is set when the waste reaches the end-of-waste state. The impacts of waste treatment from production are included in Module A3. The impacts of waste treatment during end-of-life are included in Module C, where the product reaches the end-of-waste status.
- All the LCI data in Modules A2–A3 corresponds to primary data collected from the manufacturing plant and contracted suppliers, including material and energy inputs, and waste and emission outputs.
- Modules A4, A5 and B1–B7 are not declared.

System diagram:



Description of scenarios

The system boundaries cover the following modules:

A1. Raw Material Supply

- Extraction and processing of raw materials required for manufacturing the defined external windtightness membrane: Non-woven (PET), Additives and adhesives, Printing ink.
- Extraction and processing of raw materials required for packaging the 1 m² of finished product, external windtightness membrane: Film (PE), Film (PP), Cardboard, Pallet.
- Extraction and processing of raw materials of internal packaging, used for transportation between all production locations. Internal packaging includes: Film (PE), Cardboard and Pallet.
- Generation of electricity from primary energy resources to supply the production sites with energy.

A2. Transportation

- Transportation of the raw materials was modelled based on the providers specific locations and transportation via truck to the production location #1 in Germany. All materials are procured from providers within less than 800 km.
- After production, the large rolls are transported to the production location #2 for cutting of the large rolls into sales units, printing, individual packaging and labelling of the sales units. The sales units are then packed with film (PE) for transportation on pallets. The transportation of raw materials for packaging as well as the transportation of the large rolls from the production location #1 for finishing manufacturing in the production location #2 is modelled in Module A2.

A3. Manufacturing

- The core production processes which are under control of the manufacturer are depicted within the dashed lines in the system diagram. Each processing step within the system boundaries is marked with an icon and number (#1 and #2.), indicating the specific production site where it occurs.
- Manufacturing of the defined external windtightness membrane occurs in Germany.
- The production of the large membrane roll is done in the production location #1, by bonding and laminating the polymers and the non-woven.
- In location #2, the membrane is confectioned, by adding the adhesive and release film. The membrane is cut into sale units. The products are then packed on pallets for further transportation.
- Treatment of waste generated from the manufacturing processes is included in the model. The model includes processing up to the end-of-waste status or disposal of final residues including any packaging not leaving the factory gate.
- Electricity for production in module A3 is modelled with the German Residual electricity mix.

C1-C4. End of Life

- Module C2 contains the environmental impact of transportation (0.225 kg product, 130 km by truck, Diesel, 20 - 26t gross weight / 17.3t payload capacity, 50% capacity utilisation, volume capacity utilisation factor = 1) of the product to the waste treatment plant.
- The product is treated as waste in module C3 by means of incineration.
- The loads for waste treatment are mapped here until the end of the waste property is reached. Emissions are assigned to module C3.

D. Reuse, recovery, recycling potential

- Module D accounts for potential benefits as material or energy inputs for a downstream product system in the form of the energy recovered from the waste-to-energy treatment and material recovery.
- The value flows resulting from the treatment of waste (Module C3) are accounted for completely in module D as credits outside of product system.

Allocation

The production is modelled with specific data for the declared products; there are no co-products where allocation is needed. The total energy consumption for manufacturing was calculated by the manufacturer based on the maximum power consumption of the equipment, using a conservative approach. For the input of secondary material, the cut-off method is applied. Therefore, secondary materials enter the system under consideration without any environmental loads. This applies to wastepaper for cardboard production in modules A1-A3.

Cut-off criteria

The impact associated with the disregarded mass shares is less than 5% of the impact categories per module. In addition, less than 1% of the total mass and the primary energy used is cut-off. No substances or processes with high environmental relevance were cut-off. The resulting inventory fulfils EN 15804+A2 completeness requirements, covering >99% of total mass and energy inflows and at least 95% per life-cycle stage (A1-A3, C1-C4, D)

Data quality assessment

Primary data include internal production and environmental data, supplier information and energy supply. Data were checked for plausibility and consistency, with attention to completeness and alignment with ISO 14044 requirements. For the upstream processes, generic data was selected. LCI data corresponds to manufacturer-provided data, including material inputs, outputs, and energy demands. The data collection period represents the production year 2023.

Background datasets were selected from Sphera Managed LCA Content databases (Servicepack 2026.1) and are generally not older than 10 years. Overall, the data are considered representative of standard production, with good consistency and completeness.

Overall, data quality is rated as good in accordance with EN 15941, with scores of 1.7 and 2.7 for the specific data and the background datasets used, respectively. There are no inventories with poor data quality.

Climate impact of energy

The energy requirement for production has a GWP-GHG value of 0.713 kg CO₂e/kWh.

More information

- Additional information can be obtained by contacting pro clima at info@proclima.com
- LCA practitioner: brands & values GmbH, info@brandsandvalues.com

Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data variation:

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X
Geography	DE	DE	DE										GLO	GLO	GLO	GLO	GLO
Specific data used*	6%																
Variation – products*	0%																
Variation – sites*	0%																

*Based on the GWP-GHG results for modules A1–A3

Modules declared: (X = included; ND = not declared).

The table below presents the processes contributing more than 10% to the GWP-GHG results of life cycle modules A1–A3.

Process	Source type	Source	Reference year	Data category	Share of primary data, of GWP-GHG results for A1-A3
Additives	Collected data, database	pro clima, LCA FE (2026.1)	2023	Secondary data	0%
Non-woven	Collected data, database	pro clima, LCA FE (2026.1)	2023	Secondary data	0%
Total share of primary data of the processes listed in this table for GWP-GHG results in modules A1-A3					0%

The share of primary data is calculated based on GWP-GHG results. It is a simplified indicator for data quality that supports the use of more primary data, to increase the representativeness of and comparability between EPDs. Note that the indicator does not capture all relevant aspects of data quality and is not comparable across product categories.

Variation in the results of individual products compared to the representative product is 0%.

Environmental performance

LCA results of the product(s) – main environmental performance results

EN 15804 +A2 (based on EF 3.1) characterisation factors provided in LCA for Experts were applied. Biogenic CO₂ and materially bound primary energy were adjusted manually based on the composition of the declared unit.

The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins and/or risks.

The results of the end-of-life stage (modules C1–C4) should be considered when using the results of the product stage (modules A1–A3).

The biogenic carbon and primary energy leaving the product system in module A5 have been balanced out already in modules A1–A3.

Mandatory impact category indicators according to EN 15804

Potential environmental impact – mandatory indicators according to EN 15804

Results per functional or declared unit							
Indicator	Unit	Tot. A1–A3	C1	C2	C3	C4	D
GWP-fossil	kg CO ₂ eq.	8.55E-01	0.00E+00	3.19E-03	4.93E-01	0.00E+00	-1.67E-01
GWP-biogenic	kg CO ₂ eq.	3.49E-03	0.00E+00	3.81E-06	2.53E-05	0.00E+00	-8.55E-04
GWP-luluc	kg CO ₂ eq.	5.02E-04	0.00E+00	1.35E-05	5.11E-06	0.00E+00	-2.12E-04
GWP-total	kg CO ₂ eq.	8.59E-01	0.00E+00	3.21E-03	4.93E-01	0.00E+00	-1.68E-01
ODP	kg CFC 11 eq.	2.37E-11	0.00E+00	1.49E-15	8.18E-14	0.00E+00	-3.08E-12
AP	mol H ⁺ eq.	1.33E-03	0.00E+00	6.28E-06	1.45E-04	0.00E+00	-2.16E-04
EP-freshwater	kg P eq.	3.30E-06	0.00E+00	7.99E-09	3.76E-09	0.00E+00	-7.84E-08
EP-marine	kg N eq.	4.16E-04	0.00E+00	2.69E-06	6.39E-05	0.00E+00	-6.31E-05
EP-terrestrial	mol N eq.	4.52E-03	0.00E+00	2.92E-05	7.84E-04	0.00E+00	-7.29E-04
POCP	kg NMVOC eq.	1.81E-03	0.00E+00	5.78E-06	1.66E-04	0.00E+00	-1.64E-04
ADP-minerals&metals	kg Sb eq.	1.60E-07	0.00E+00	2.28E-10	7.47E-10	0.00E+00	-2.04E-08
ADP-fossil*	MJ	2.02E+01	0.00E+00	4.11E-02	9.77E-02	0.00E+00	-2.85E+00
WDP	m ³	8.62E-02	0.00E+00	1.28E-05	4.58E-02	0.00E+00	-1.38E-02
Acronyms	GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption						

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.

Potential environmental impact – additional mandatory and voluntary indicators

Results per functional or declared unit							
Indicator	Unit	Tot. A1–A3	C1	C2	C3	C4	D
GWP-GHG ¹	kg CO ₂ eq.	8.56E-01	0.00E+00	3.20E-03	4.93E-01	0.00E+00	-1.67E-01
PM	Disease incidence	1.30E-08	0.00E+00	5.29E-11	4.92E-10	0.00E+00	-1.79E-09
IR	kBq U235 eq.	2.81E-02	0.00E+00	8.44E-06	5.59E-04	0.00E+00	-2.78E-02
ETP-fw	CTUe	9.40E+00	0.00E+00	3.54E-02	3.32E-02	0.00E+00	-3.38E-01
HTP-c	CTUh	2.22E-10	0.00E+00	7.01E-13	2.86E-12	0.00E+00	-2.85E-11
HTP-nc	CTUh	7.17E-09	0.00E+00	3.64E-11	2.87E-11	0.00E+00	-6.78E-10
SQP	dimensionless	3.56E+00	0.00E+00	1.10E-02	2.51E-02	0.00E+00	-5.52E-01
Acronyms	GWP-GHG = This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO ₂ is set to zero; PM = Particulate matter emissions; IR = Ionizing radiation, human health; ETP-fw = Eco-toxicity – freshwater; HTP-c = Human toxicity, cancer effect; HTP-nc = Human toxicity, non-cancer effects; SQP = Land use related impacts/Soil quality						

¹ This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO₂ is set to zero.

Resource use indicators

Results per functional or declared unit							
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
PERE	MJ	2.23E+00	0.00E+00	2.93E-03	2.54E-02	0.00E+00	-1.01E+00
PERM	MJ	1.42E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT	MJ	2.23E+00	0.00E+00	2.93E-03	2.54E-02	0.00E+00	-1.01E+00
PENRE	MJ	1.48E+01	0.00E+00	4.11E-02	5.36E+00	0.00E+00	-2.85E+00
PENRM	MJ	5.40E+00	0.00E+00	0.00E+00	-5.26E+00	0.00E+00	0.00E+00
PENRT	MJ	2.02E+01	0.00E+00	4.11E-02	9.77E-02	0.00E+00	-2.85E+00
SM	kg	5.05E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	m ³	4.31E-03	0.00E+00	9.14E-07	1.08E-03	0.00E+00	-6.41E-04
Acronyms	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water						

Waste indicators

Results per functional or declared unit							
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Hazardous waste disposed	kg	2.28E-08	0.00E+00	1.90E-12	5.24E-11	0.00E+00	-2.02E-09
Non-hazardous waste disposed	kg	1.53E-02	0.00E+00	7.92E-06	2.56E-03	0.00E+00	-1.51E-03
Radioactive waste disposed	kg	2.12E-04	0.00E+00	6.47E-08	3.78E-06	0.00E+00	-1.82E-04

Output flow indicators

Results per functional or declared unit							
Indicator	Unit	A1-A3	C1	C2	C3	C4	D
Components for re-use	kg	5.75E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Material for recycling	kg	2.29E-04	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy, electricity	MJ	0.00E+00	0.00E+00	0.00E+00	7.63E-01	0.00E+00	0.00E+00
Exported energy, thermal	MJ	0.00E+00	0.00E+00	0.00E+00	1.38E+00	0.00E+00	0.00E+00

Abbreviations

CAS No.	Chemical Abstracts Service Number
CEN	European Committee for Standardization
CFC-11 eq.	Chlorofluorocarbon-11 Equivalents
CO ₂ eq.	Carbon Dioxide Equivalents
EF 3.1	Environmental Footprint 3.1 characterization factors
EN	European Norm (Standard)
EPD	Environmental Product Declaration
EU	Europe
GLO	Global
GPI	General Programme Instructions
ISO	International Organization for Standardization
kg	Kilogram
kg C	Kilograms of Carbon
kg CO ₂ eq.	Kilograms of Carbon Dioxide Equivalent
LCA	Life Cycle Assessment
LCI	Life Cycle Inventory
m ³	Cubic Meter
MJ	Megajoule
MNR	Module Not Relevant
N eq.	Nitrogen Equivalents
ND	Not Declared
NM VOC	Non-Methane Volatile Organic Compounds
P eq.	Phosphorus Equivalents
PCR	Product Category Rules
RSL	Reference service life
Sb eq.	Antimony Equivalents
SVHC	Substances of Very High Concern
Environmental impact indicators (EN 15804)	
GWP	Global Warming Potential
GWP-GHG	Global Warming Potential for greenhouse gases (kg CO ₂ eq.)
EP	Eutrophication Potential
GWP-total	Total Global Warming Potential(kg CO ₂ eq.)
GWP-fossil	Global Warming Potential from fossil (kg CO ₂ eq.)
GWP-biogenic	Global Warming Potential biogenic (kg CO ₂ eq.)
GWP-luluc	Global Warming Potential land use and land use change (kg CO ₂ eq.)
ODP	Ozone Depletion Potential (kg CFC-11 eq.)
AP	Acidification potential,(mol H ⁺ eq.)
EP-freshwater	Freshwater eutrophication potential (kg P eq.)
EP-marine	Marine eutrophication potential (kg N eq.)
EP-terrestrial	Terrestrial eutrophication potential (mol N eq.)
POCP	Photochemical Ozone Creation Potential (kg NM VOC eq.)
ADP	Abiotic Depletion Potential
ADP-minerals&metals	Abiotic depletion potential for non-fossil resources (kg Sb eq.)
ADPF	Abiotic depletion potential for fossil resources (MJ)
WDP	Water Deprivation Potential (m ³)
PERE	Renewable primary energy (excluding as raw materials) (MJ)
PERM	Renewable primary energy used as raw materials (MJ)
PERT	Total renewable primary energy (MJ)
PENRE	Non-renewable primary energy (excluding as raw materials) (MJ)
PENRM	Non-renewable primary energy used as raw materials (MJ)
PENRT	Total use of non-renewable primary energy resources (MJ)
SM	Use of secondary material (kg)

RSF	Use of renewable secondary fuels (MJ)
NRSF	Use of non-renewable secondary fuels (MJ)
FW	Use of net fresh water (m3)
HWD	Hazardous waste disposed (kg)
NHWD	Non-hazardous waste disposed (kg)
RWD	Radioactive waste disposed (kg)
CFR	Components for Reuse (kg)
MR	Material for Recycling (kg)
MER	Materials for Energy Recovery (kg)
EEE	Exported Energy, Electricity (MJ)
EET	Exported Energy, Thermal (MJ)

References

- ASTM E96, Standard test methods for water vapor transmission of materials, 2017. <https://dx.doi.org/10.1520/E0096-00E01>
- DIN EN ISO 14025 Environmental labels and declarations – Type III environmental declarations – Principles and procedures; 2009-11.
- DIN EN ISO 14044 Environmental management – Life cycle assessment – Requirements and guidelines (ISO 14044:2006); German and English version EN ISO 14044:2006
- EAD 030218-01-0402, European Assessment Document for Membranes for use as roof or wall underlays or both, March 2019. https://www.eota.eu/download?file=/2018/18-03-0469/for%20jeu/ead%20030218-01-0402_ojeu%202023.pdf
- EN 1109:2013-07, Flexible sheets for waterproofing – Bitumen sheets for roof waterproofing – Determination of flexibility at low temperature, 2013. <https://dx.doi.org/10.31030/2007324>
- EN 1296:2001-03, Flexible sheets for waterproofing – Bitumen, plastic and rubber sheets for roof waterproofing – Method for artificial ageing by long term exposure to elevated temperature, 2001. <https://dx.doi.org/10.31030/9115025>
- EN 1297:2004-12, Flexible sheets for waterproofing – Bitumen, plastic and rubber sheets for roof waterproofing – Method of artificial ageing by long term exposure to the combination of UV radiation, elevated temperature and water, 2004. <https://dx.doi.org/10.31030/9185565>
- EN 13501-1:2019-05, Fire classification of construction products and building elements – Part 1: Classification using data from reaction to fire tests, 2019. <https://dx.doi.org/10.31030/2870379>
- EN 13583:2012-10, Flexible sheets for waterproofing – Bitumen, plastic and rubber sheets for roof waterproofing – Determination of hail resistance, 2012. <https://dx.doi.org/10.31030/1905079>
- EN 13859-1:2014-07, Flexible sheets for waterproofing – Definitions and characteristics of underlays – Part 1: Underlays for discontinuous roofing, 2014. <https://dx.doi.org/10.31030/2143338>
- EN 15976:2011-07, Flexible sheets for waterproofing – Determination of emissivity, 2011. <https://dx.doi.org/10.31030/1733297>
- EN 1849-2:2019-09, Flexible sheets for waterproofing – Determination of thickness and mass per unit area – Part 2: Plastics and rubber sheets for roof waterproofing, 2019. <https://dx.doi.org/10.31030/3042454>
- EN ISO 12572:2017-05, Hygrothermal performance of building materials and products – Determination of water vapour transmission properties – Cup method (ISO 12572:2016), 2017. <https://dx.doi.org/10.31030/2429972>
- EN ISO 811:2018-08, Textiles – Determination of resistance to water penetration – Hydrostatic pressure test (ISO 811:2018), 2018. <https://dx.doi.org/10.31030/2807631>
- EPD International Product Category Rules PCR 2019:14 Construction Products version 2.0.1. Published on 2025-06-05.
- EPD International General program instructions for the International EPD System Version 5.0.1. Published on 2025-02-27.
- German Institute of Construction Engineering (DIBt), ETA-23/0532, European Technical Assessment: SOLITEX QUANTHO 3000 connect – Membranes for use as roof underlays, 4 December 2023. <https://www.dibt.de/de/service/zulassungsdownload/detail/eta-230532>
- ISO 14001 Environmental management systems – Requirements with guidance for use (ISO 14001:2015); German and English version EN ISO 14001:2015
- LCA for Experts (GaBi), LCA for Experts 10.9: Software System and Database for Life Cycle Engineering. Service pack 2026.1. 1992-2023. Sphera Solutions.
- Produktdatenblatt für Unterdeckbahnen und Unterspannbahnen (Product datasheet für roofing underlay membranes), 2024. Published by Zentralverband des Deutschen Dachdeckerhandwerks (Central Association of the German Roofing Trade).
- Test regulations for hail impact resistance published by the Swiss Association of Cantonal Fire Insurance Institutes (VKF/AEAI).
- TRACI Bare. J. C. Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI). Version 2.2 – User's Manual; EPA/600/R-12/554 2012.

Version history

Version 1, 2026-09-30

Original Version of the EPD

Version 2, 2026-10-08

Differences versus the previously published version:

- Correction of the "LCA Information" section under "A3. Manufacturing" by deleting the sentence "Includes the effects of producing an additional 8% membrane (overlap) to ensure airtightness per square meter of installed membrane."



pro clima / MOLL bauökologische Produkte GmbH

www.proclima.com

www.environdec.com

 **EPD**
INTERNATIONAL EPD SYSTEM

