

Installation instructions

TESCON® **NAIDECK**

Installation steps



1. Reliable sealing

Adhesive with excellent sealing pro clima TESCO NAIDECK has a very free-flowing butyl adhesive. This adhesive penetrates deep into the structure of membranes and wood-fibre boards and seals nail holes permanently and securely.



2. Apply the tape

For permanently sealed nail and screw holes, centre the butyl rubber tape on the counter batten and gradually stick it in place. This step can be carried out in a manner that is kinder to your hands by using the pro clima PRESSFIX application tool.



3. Attach the batten

Start to pull off the release film at one end.
Put the counter batten in place and fasten at one point with a nail.
Make sure that the end of the release film is protruding from the side of the joint.



4. Gradually remove the release film

Gradually pull the release film out of the joint. Gradually fasten the counter batten using nails or screws. You're finished!

General conditions

IMPORTANT INFORMATION

- Self-sealing when compressed between two rigid materials. Screw and nail penetrations will be sealed during the fixing process.
- Proven to enhance resistance to driving rain through fixings on WRB penetrations in facade tests, according to AS/NZS 4284.
- Pro Clima strongly recommends the use of TESCO® NAIDECK on roof systems below 10°.

PRODUCT DESCRIPTION

TESCON® NAIDECK is a double-sided, self-sealing strip for use on the underside of purlins & battens fixed directly to your roofing WRB or facade, where any attachment is fixed to your WRB layer and requires a penetration. Made from butyl, it has excellent self-sealing properties.

WEATHER EXPOSURE

This product is not designed for direct exposure to UV, direct contact with metal cladding or facades, or face sealed systems. Ideally, it is used in ventilated facades separated from direct contact with the cladding, using thermal breaks or timber. Exterior cladding should be detailed to prevent direct sunlight from reaching TESCO® NAIDECK in service.

APPLICATION NOTES

This product should be applied to the batten, purlin, clip, mount or the like before installing in the correct position.

© 2024 Pro Clima New Zealand. All rights reserved. The trademarks in this document are registered to Pro Clima or one or more of its affiliates.

The information provided in this document is based on practical experience and current knowledge and was correct at the time of publication. Pro Clima reserves the right to change technical details as developments occur and improvements are made to our products.

Pro Clima recommends reviewing the latest technical data on the www.proclima.co.nz [https://www.proclima.co.nz] website to ensure the most current document version.

PRO CLIMA NEW ZEALAND

Upper North Island: 09 892 9900 [tel:006498929900]

Lower North Island: 04 589 8460 [tel:006445898460]

South Island: 03 327 4925 [tel:006433274925]

Technical: support@proclima.co.nz [mailto:support@proclima.co.nz]

General: welcome@proclima.co.nz [mailto:welcome@proclima.co.nz]

0800 PRO CLIMA (776 254) [tel:0064800776254]