



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 1 of 19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TESCON SPRIMER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

sprayable primer

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	MOLL bauökologische Produkte GmbH proclima	
Street:	Rheintalstraße 35 - 43	
Place:	D-68723 Schwetzingen	
Telephone:	+49 (0) 6202 2782-0	Telefax: +49 (0) 6202 2782-21
e-mail:	info@proclima.de	
e-mail (Contact person):	info@proclima.de	
Internet:	http://www.proclima.de	
Responsible Department:	info@proclima.de	

1.4. Emergency telephone number: +49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1907/2006

Hazard categories:

Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1907/2006

Hazard components for labelling

methyl acetate

ethyl acetate

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 2 of 19

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist/vapours/spray.
P262	Do not get in eyes, on skin, or on clothing.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable
insufficient ventilation: Vapours can form explosive mixtures with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 3 of 19

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
79-20-9	methyl acetate			20-30 %
	201-185-2	607-021-00-X	01-2119459211-47	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			1-10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			1-10 %
	265-151-9	649-328-00-1	01-2119475133-43	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			1-10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
110-54-3	n-hexane			<0,5 %
	203-777-6	601-037-00-0	01-2119480412-44	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			
128-37-0	2,6-di-tert-butyl-p-kresol			<0,5 %
	204-881-4		01-2119555270-46	
	Eye Irrit. 2, Aquatic Acute 1, Aquatic Chronic 1; H319 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
79-20-9	201-185-2	methyl acetate	20-30 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = 6482 mg/kg		
141-78-6	205-500-4	ethyl acetate	1-10 %
	dermal: LD50 = > 20000 mg/kg; oral: LD50 = 4934 mg/kg		
64742-49-0	265-151-9	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	1-10 %
	inhalation: LC50 = > 4,96 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	1-10 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg		
110-54-3	203-777-6	n-hexane	<0,5 %
	inhalation: LC50 = 73860 mg/l (vapours); dermal: LD50 = > 2000 mg/kg STOT RE 2; H373: >= 5 - 100		
128-37-0	204-881-4	2,6-di-tert-butyl-p-kresol	<0,5 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 6000 mg/kg M acute; H400: M=1 M chron.; H410: M=1		



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 4 of 19

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

Further Information

No information available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Remove contaminated, saturated clothing immediately.

Remove casualty to fresh air and keep warm and at rest.

After inhalation

Remove person to fresh air and keep comfortable for breathing.

In case of respiratory tract irritation, consult a physician.

If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person or a person with cramps.

Call a doctor if you feel unwell.

Do NOT induce vomiting.

Observe risk of aspiration if vomiting occurs.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Dry extinguishing powder, alcohol resistant foam, Carbon dioxide (CO₂), Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting.

In case of fire may be liberated: Gases/vapours, toxic

5.3. Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 5 of 19

Additional information

- Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
- Dispose of waste according to applicable legislation.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- See protective measures under point 7 and 8.
- Wear personal protection equipment (refer to section 8).
- Do not breathe mist/vapours/spray. Use appropriate respiratory protection.
- Keep away from sources of ignition - No smoking.
- Provide adequate ventilation.

For non-emergency personnel

- Remove persons to safety.

For emergency responders

- No data available

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Handling larger quantities: In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

- Take up mechanically, placing in appropriate containers for disposal.

For cleaning up

- Water (with cleaning agent)

Other information

- Provide adequate ventilation.
- Do not pierce or burn, even after use.
- Collect in closed and suitable containers for disposal.

6.4. Reference to other sections

- See protective measures under point 7 and 8.
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Wear personal protection equipment (refer to section 8).
- Remove contaminated, saturated clothing immediately.
- Avoid contact with eyes and skin.
- Provide adequate ventilation.
- In case of inadequate ventilation wear respiratory protection.
- Avoid release to the environment.

Advice on protection against fire and explosion

- Do not spray on an open flame or other ignition source.
- Keep away from sources of ignition - No smoking.
- Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 6 of 19

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection.
Wash hands and face before breaks and after work and take a shower if necessary.
When using do not eat, drink, smoke, sniff.
Only wear fitting, comfortable and clean protective clothing.
Take off contaminated clothing and wash it before reuse.
Avoid contact with eyes and skin.

Further information on handling

After use replace the closing cap immediately.
Observe instructions for use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

To follow: Betriebssicherheitsverordnung (BetrSichV)
Keep container tightly closed in a cool, well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Pressurised container: May burst if heated.
Keep out of reach of children.
Keep locked up and out of reach of children.

Hints on joint storage

Keep away from:
Food and feedingstuffs

Further information on storage conditions

Keep away from:
Frost
Heat
Humidity
Store small packages in a suitable, robust cabinet. Only allow access to authorised staff.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 7 of 19

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
79-20-9	methyl acetate			
Worker DNEL, long-term		inhalation	systemic	610 mg/m ³
Worker DNEL, long-term		inhalation	local	305 mg/m ³
Worker DNEL, long-term		dermal	systemic	88 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	131 mg/m ³
Consumer DNEL, long-term		inhalation	local	152 mg/m ³
Consumer DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	44 mg/kg bw/day
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m ³
Worker DNEL, acute		inhalation	systemic	1468 mg/m ³
Worker DNEL, long-term		inhalation	local	734 mg/m ³
Worker DNEL, acute		inhalation	local	1468 mg/m ³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m ³
Consumer DNEL, acute		inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term		inhalation	local	367 mg/m ³
Consumer DNEL, acute		inhalation	local	734 mg/m ³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			
Worker DNEL, long-term		inhalation	systemic	1,9 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	0,41 mg/m ³
Worker DNEL, acute		inhalation	systemic	1286,4 mg/m ³
Worker DNEL, long-term		inhalation	local	837,5 mg/m ³
Worker DNEL, acute		inhalation	local	1066,67 mg/m ³
Consumer DNEL, acute		inhalation	systemic	1152 mg/m ³
Consumer DNEL, long-term		inhalation	local	178,57 mg/m ³
Consumer DNEL, acute		inhalation	local	640 mg/m ³
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Consumer DNEL, long-term		inhalation	systemic	447 mg/m ³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2085 mg/m ³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
110-54-3	n-hexane			
Worker DNEL, long-term		inhalation	systemic	75 mg/m ³
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 8 of 19

Consumer DNEL, long-term	dermal	systemic	5,3 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	16 mg/m ³
128-37-0	2,6-di-tert-butyl-p-kresol		
Worker DNEL, long-term	inhalation	systemic	3,5 mg/m ³
Worker DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,86 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day

PNEC values

CAS No	Substance	Value
Environmental compartment		
79-20-9	methyl acetate	
Freshwater		0,12 mg/l
Freshwater (intermittent releases)		1,2 mg/l
Marine water		0,012 mg/l
Freshwater sediment		0,128 mg/kg
Marine sediment		0,013 mg/kg
Secondary poisoning		20,4 mg/kg
Micro-organisms in sewage treatment plants (STP)		600 mg/l
Soil		0,042 mg/kg
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Freshwater (intermittent releases)		1,65 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		200 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
128-37-0	2,6-di-tert-butyl-p-kresol	
Freshwater		0,000199 mg/l
Freshwater (intermittent releases)		0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater sediment		0,0996 mg/kg
Marine sediment		0,00996 mg/kg
Secondary poisoning		8,33 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,17 mg/l
Soil		0,04769 mg/kg



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 9 of 19

Additional advice on limit values

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha;
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics;
DFG: MAK- und BAT-Werte-Liste 2021
Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe (Mitteilung 57)
vgl. Abschnitt Xb

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.
Work in well-ventilated zones or use proper respiratory protection.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: DIN EN 166
goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374 The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material $\geq 0,4$ mm NBR (Nitrile rubber)

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Extremely flammable aerosol. Pressurized container: May burst if heated.

Environmental exposure controls

Keep container tightly closed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosols
Colour:	colourless
Odour:	characteristic

Changes in the physical state

Boiling point or initial boiling point and boiling range:	No data available
---	-------------------

Flash point:	-60 °C
--------------	--------

Flammability



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 10 of 19

Solid/liquid: No data available
Gas: No data available

Explosive properties

not explosive according to EU A.14
In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 0,6 vol. %
Upper explosion limits: 16 vol. %
Auto-ignition temperature: 365 °C

Self-ignition temperature

Solid: No data available
Gas: No data available

Decomposition temperature: No data available

Oxidizing properties

No data available

pH-Value: No data available

Viscosity / dynamic: No data available

Viscosity / kinematic: No data available

Water solubility: Immiscible

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available

Vapour pressure: 3900 hPa
(at 20 °C)

Density (at 20 °C): 0,71 g/cm³

Relative vapour density: No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: No data available

Other safety characteristics

Solvent content: 79,6%

Solid content: 0,1%

Evaporation rate: No data available

Further Information

VOC: 79,61%

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Closed containers may burst when pressure and temperature rise



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 11 of 19

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Do not spray on an open flame or other ignition source.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

Further information

No further relevant information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No. 1907/2006

Acute toxicity

Based on available data, the classification criteria are not met.



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 12 of 19

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
79-20-9	methyl acetate				
	oral	LD50 6482 mg/kg	Rat	Publication (1962)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	EU Method B.3
141-78-6	ethyl acetate				
	oral	LD50 4934 mg/kg	Rabbit	Ind. Med. Vol. 41, No.4, 31 - 33 (1972)	OECD Guideline 401
	dermal	LD50 > 20000 mg/kg	Rabbit	Am Ind Hyg Ass J, 23, 95 (1962)	Similar to one day cuff method of Draize
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1986)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 4,96 mg/l	Rat	Study report (1992)	OECD Guideline 403
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics				
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403
110-54-3	n-hexane				
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	
	inhalation (4 h) vapour	LC50 73860 mg/l	Rat	Industrial Medicine, Vol. 39, No. 5, May	OECD Guideline 403
128-37-0	2,6-di-tert-butyl-p-kresol				
	oral	LD50 > 6000 mg/kg	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (methyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 13 of 19

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Further information

No further relevant information available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 14 of 19

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
79-20-9	methyl acetate					
	Acute algae toxicity	ErC50 > 120 mg/l	72 h	Desmodemus subspicatus	Study report (1994)	EU Method C.3
	Acute crustacea toxicity	EC50 1026,7 mg/l	48 h	Daphnia magna	Study report (1994)	OECD Guideline 202
	Acute bacteria toxicity	(6100 mg/l)	0,5 h	Photobacterium phosphoreum	Bayr. Landesamt für Wasserwirtschaft (19)	Method: other: Mikrotoxtest
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50 230 mg/l	96 h	Pimephales promelas	Publication (1984)	other: US EPA method E03-05
	Fish toxicity	NOEC < 9,65 mg/l	32 d	Pimephales promelas	http://www.epa.gov/ecotox (1992)	OECD Guideline 210
	Algae toxicity	NOEC >100 mg/l	3 d	Desmodemus subspicatus		OECD 201
	Crustacea toxicity	NOEC 2,4 mg/l	21 d	Daphnia magna	Water Research 23: 501-510. (1989)	other: see principles of method below
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha					
	Acute fish toxicity	LL50 8,2 mg/l	96 h	Pimephales promelas	Study report (1995)	other: EPA 66013-75-009
	Acute algae toxicity	ErC50 3,1 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50 4,5 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202
	Fish toxicity	NOEC 2,6 mg/l	21 d	Daphnia magna	Study report (1999)	other: OECD Guideline 211
	Crustacea toxicity	NOEC 2,6 mg/l	21 d	Daphnia magna	Study report (1999)	OECD Guideline 211
	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LL50 > 13,4 mg/l	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203
	Acute algae toxicity	ErC50 12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EC50 3 mg/l	48 h	Daphnia magna	OECD Guideline 202	
	Fish toxicity	NOEC 1,534 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211
110-54-3	n-hexane					
	Acute fish toxicity	LL50 12,51 mg/l	96 h	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 15 of 19

	Acute algae toxicity	ErC50 mg/l	9,285	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EL50 mg/l	21,85	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC	2,8 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	4,888	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
128-37-0	2,6-di-tert-butyl-p-kresol						
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACH Registration Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACH Registration Dossier	OECD Guideline 210
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACH Registration Dossier	OECD Guideline 211
	Acute bacteria toxicity	(> 10000 mg/l)		3 h	Activated sludge	Study report (2000)	OECD Guideline 209

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No further relevant information available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
79-20-9	methyl acetate	0,18
141-78-6	ethyl acetate	0,68
110-54-3	n-hexane	4
128-37-0	2,6-di-tert-butyl-p-kresol	5,03

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus melanotus	Chemosphere 14, 1589
110-54-3	n-hexane	501,187	Pimephales promelas	QSAR in Environmenta
128-37-0	2,6-di-tert-butyl-p-kresol	598,4	Cyprinus carpio	REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 16 of 19

not applicable

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

Further information

obviously hazardous to water

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Dispose of waste according to applicable legislation.

Hazardous waste according to Directive 2008/98/EC (waste framework directive).

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. (AVV 160504, 150110, 150104)

Dispose of waste according to applicable legislation.

Completely emptied packages can be recycled. (AVV 150104)

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1950
<u>14.2. UN proper shipping name:</u>	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2
<u>14.4. Packing group:</u>	-
Hazard label:	2.1



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 17 of 19

Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Special Provisions: 63, 190, 277, 327, 344, 381,959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1
Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29

2010/75/EU (VOC): 79,6%

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information

Classification according to Regulation (EC) No 1272/2008 [CLP]



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 18 of 19

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Aerosol directive (75/324/EEC)
DECISIONS COMMISSION DECISION of 18 December 2014 amending Decision 2000/532/EC on the list of waste pursuant to Directive 2008/98/EC of the European Parliament and of the Council
DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives
DIRECTIVE (EU) 2018/851 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 30 May 2018 amending Directive 2008/98/EC on waste

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 2 - obviously hazardous to water

Additional information

Germany:
TRGS 220, TRGS 400 ff, TRGS 500, TRGS 510, TRGS 555, TRGS 600, TRGS 720ff., TRGS 900, TRGS 903
Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
methyl acetate
ethyl acetate
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
n-hexane
2,6-di-tert-butyl-p-kresol

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,3,6,7,8,10,11,13,15.

Abbreviations and acronyms

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent



Safety Data Sheet

according to Regulation (EC) No. 1907/2006

TESCON SPRIMER

Revision date: 18.01.2022

Page 19 of 19

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)