

pro clima Adhesion Matrix

All pro clima membranes, tapes and adhesives are designed to be compatible with one another. Optimum long-term durability for weathertightness and airtightness depends on the quality of connections between pro clima products and other building materials. The table below provides guidance when forming connections to common building materials.

		SOLITEX ADHERO® range	TESCON EXTORA®	TESCON EXTORA® PROFIL	TESCON® VANA	TESCON® PROFIL	ORCON® EXTONSEAL	ORCON® CLASSIC	CONTEGA® MULTIBOND	CONTEGA® EXO	CONTEGA® SOLIDO EXO-D	AEROSANA® SOLIDO SL-D	KAFLEX monolduo	ROFLEX	DUPLEX
Timber, OSB, Plywood	dirty*					✓					✓				
	clean*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				
Plasterboard	clean*	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓			
Paint Primers		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓
AEROSANA® VISCONN	dry / clean*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
PIR Polyisocyanurate	on foil	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	
	on PIR														
XPS Extruded Polystyrene	clean*	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	
EPS Expanded Polystyrene	clean*	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	
Expanded foams	dry												✓		
Cement / Gypsum plaster	smooth*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough*							✓	✓				✓		
	friable*											✓			
Acrylic plaster	smooth*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	rough*							✓	✓			✓			
Steel	galvanised	✓	✓	✓	✓	✓	✓	✓		✓	✓				✓
	bright	✓	✓	✓	✓	✓	✓	✓		✓	✓				✓
	painted	✓	✓	✓	✓	✓	✓	✓		✓	✓				✓
Aluminium	clean	✓	✓	✓	✓	✓	✓	✓		✓	✓				✓
Brickwork	rough*	✓	✓	✓	✓	✓	✓	✓				✓			
	friable*											✓			
Dampcourse	aluminium							✓	✓						
	polyethylene							✓	✓						
Concrete	smooth*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	rough*							✓	✓			✓			
	blockwork*	✓													
Fibre cement	clean*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	friable*											✓			
Windows	aluminium	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓
	PVC	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓
	timber	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓
Cables	flat		✓	✓	✓	✓	✓	✓		✓	✓				
	round		✓	✓	✓	✓	✓	✓		✓	✓				

* TESCON® PRIMER RP can be used to promote surface adhesion